to be conveyed to

Being situated in the Southeast quarter of Section 22 Town 6 south, Range 8 East, Stokes Township, Logan county, Ohio, and being more fully described as follows;

Beginning at an iron pin in the center of County Highway #87 at the Southwest corner of said Southeast quarter section at station 185 + 74.5 as shown on page 39 of the Logan County angineers Field Book # 572; thence with the center of said County Highway #87, and the south line of said section 22, N 88°-43' E 125.00 feet to an iron pin; thence N 1°-20' W 145.00 feet to an iron pipe and crossing an iron pipe at 20.00 feet; thence S 88°-43' & 125.00 feet to an iron pipe; thence S 1°-20' E 145.00 feet to the place of beginning and crossing an iron pipe at 125.00 feet. Said tract contains 0.416 acres more or less.

I hereby certify that the above tract is a true representation of a survey made be me on January 9, 1960.

William H. Lewis

Registered Surveyor 44465

on Or States

3156 -1D-1

to be conveyed to STANELY B. TAYLOR

Being situated in the Southeast quarter of Section 22, Town 6 South, Range 8 Last, Stokes Township, Logan Bounty, Ohio, and being more fully described as follows;

Beginning at an iron pin in the center of County Highway #87 at the Southwest corner of said Southeast quarter section at station 185 + 74.5 as shown on page 39 of the Logan Courty Engineer's Field book #572; thence with the senter of said County Highway #87 and the South line of said Section 22 N 86°-43' E FREE 125.00 feet to an iron pin which pin is the true place of beginning of this tract; thence Bontimuing N 88°-43' E 125.00 feet to an iron pin; thence N 1°-20' W 145.00 feet to an iron pipe and crossing an iron pin; thence N 1°-20' W 145.00 feet to an iron pipe and crossing an iron pipe at 20.00 feet; thence S 88°-43' W 125.00 feet to an iron pipe; thence S 1°-20' E 145.00 feet to the true place of beginning and crossing # and crossing an iron i e at 125.00 feet; said tract dontains 0.416 acres more or less.

I hereby certify that the above description is a correct representation of a survey made by he on January 9, 1960.

William H. Lewis Registered Surveyor 34465

1st tract last of reposed Taylor Tract

Being situated in the Southeast quarter of cSection 22 , Town 6 South, Hange 8 sast, Stokes Township, Logan County, Ohio and being more fully described as follows;

Beginning at an iron pin in the center of County Highway #87 at the Southwest corner of said Southeast quarter section at station 185 + 74.5 as shown on page 39 of the Logar County Engineer's Field Book #572; thence with the center of said Highway #87 and the south lime of Said Section 22, N 58°-43' E 250.00 feet to an iron pin, which pin is the true place of beginning for this tract; thence continuing N 58°-43' E 125.00 feet to and iron pipe; thence N 1°-20' W 145.00 feet to an iron pipe and crossing aniron pipe at 20.00 feet; thence S 88°-43' W 125.00 feet to an iron pipe; thence S 1°-20' E 145.00 feet to the true place of beginning and crossing an iron pipe at 125.00 feet. Said tract contains 0.416 acres more or less.

The above description is a true representation of a survey made be me on January 9, 1960 for Russell Van Horm.

William H. Lewis
Registered Surveyor #4465

2nd tract East of roposed Taylor Tract

Being situated in the Southeast quarter of section 22, Town 6 south, Range 8 East, Stokes Township, Logan County, Ohio and being more fully described as follows;

Beginning at an iron pin in the center of County Highway #87 at the Southwest corner of said Southeast quarter section at station 185 + 74.5 as shown on page 39 of the Logan County Engineer's Field Book #572; thence with the center of said County Highway #87 and the South line of Section 22 N 88°-43' E 375.00 feet to an iron pin which pin is the true ph ce of beginning for this tract; thence continuing N 88°-43' E 125.00 feet to an iron pin; thence N 1°-20' W 145.00 feet to an iron pipe and crossing an iron pipe; thence S 1°-20' E 145.00 feet to the true place of beginning and crossing an iron pipe at 125.00 feet. Said tract contains 0.416 acres more or less.

The above description is a true representation of a survey made by me on January 9, 1960 for Russell Van Horn.

William H. Lewis

Registered Surveyor #4465

on Plat Book

On D.E.G.
2/22/6/

Tract 5 for Russell Van Horn

Being situated in the Southeast quarter of section 22, Town 6 South, Range 8 East, Stokes Township, Logan County, Chio and being more fully described as follows:

Beginning at an iron bar in the center of County Highway #87 at the Southwest corner of said Southeast quarter section at Station 185+74.5 as shown on page 39 of the Logan County Engineers field book #572; thence with center of said County Highway #87 and the south line of said section 22, N 88°43' E 500.00 feet to an iron pipe, which pipe is the true place of beginning for this tract; thence continuing N 88°-43' E 125.00 feet to an iron pipe; thence N 1°-20' W 145.00 feet to an iron pipe and crossing an iron pipe at E 20.00 feet; thence S 88° 43' W 125.00 feet to an iron pipe; thence S 1°-20' E 145.00 feet to the true place of beginning and crossing an iron pipe at 125.00 feet. Said tract contains 0.416 acres more or less.

I hereby certify that the above description is a true representation of a survey made by me on October 15, 1960 and that all irons a s called for have been placed.

William H. Lewis Registered Surveyor #4465

